



Environmental
Remediation Equipment Inc.™

6 Gas, Sample Draw With PID, IR & Super Toxics

GX-6000

Simply put, the GX-6000 is a game changer. This powerful hand-held instrument is capable of simultaneously monitoring up to 6 gases. In addition to the standard 4 confined space gases which include combustibles, O₂, CO, & H₂S, the GX-6000 has 2 additional smart channels that accept PID, IR or super toxic sensors. Equipped with a strong internal sample pump, a man-down alarm, a panic alarm, an LED flashlight, and large auto rotating LCD display, the GX-6000 can operate as a single gas PID unit or a multifunctional tool utilizing all 6 channels. The GX-6000 with a PID sensor will come equipped with a library of over 600 VOC gases to choose from as standard. Choosing from the library is easy with a personalized favorites list of 30 commonly used VOC's as well as a list of 8 of the most recently used VOC's. A benzene-specific version is available using a pre-filter tube for detecting low levels of benzene.

The GX-6000 has a rugged design built for the nastiest environments. It is equipped with a removable impact-resistant rubber boot and a dust and water resistant enclosure with an IP-67 rating. With 5 bright LED lights on 3 sides of the instrument, alarms are easily seen from a variety of perspectives. With vibration and loud audible alarm, GX-6000 will easily alert users when needed.

Features

- Monitor up to 6 gases
- 2 smart sensor slots auto recognize PID, IR, and super toxic sensors
- 6 Operating modes: normal, leak check, benzene select mode, inert, snap log and bar hole
- Library of over 600 VOCs
- PPM Leak Check mode
- Man-down and panic alarms
- Auto display rotation
- LED Light source
- Internal sample pump
- Glove friendly glow in the dark buttons
- Light weight, small, rugged IP-67 design
- Interchangeable battery packs Li-ion / alkaline
- Operates up to 14 hours on Li-ion battery pack, fully recharges in 3 hours
- Field replaceable sensors, batteries and filters

Applications

- Confined space entry
- Hazmat response teams
- Arson investigation
- Remediation sites
- Perimeter monitoring
- Leak detection
- Landfill monitoring
- Wing tank entry



Gases & Detectable Ranges					
Gas	Measuring Range	Reading Increment	Alarm Set Points	Accuracy (which ever is greater)	
Catalytic					
Hydrocarbons (CH₄, std)	0 - 100% LEL	1% LEL	A1: 10%LEL	± 5% of reading or A2: 50%LEL ± 2% LEL	
			A2: 50%LEL		
Galvanic					
Oxygen (O₂)	0 - 40.0% Vol.	0.1% Vol.	A1: 19.5 Vol A2: 23.5 Vol.	± 0.5% O ₂	
Electro Chemical					
Carbon Monoxide (CO)	0 - 500 ppm	1 ppm	A1: 25 ppm	± 5% of reading or ± 5 ppm	
			A2: 50 ppm		
			TWA 25 ppm		
			STEL 200 ppm		
Hydrogen Sulfide (H₂S)	0 - 100.0 ppm	0.5 ppm	A1: 5.0 ppm	± 5% of reading or ± 2 ppm	
			A2: 30.0 ppm		
			TWA 1.0 ppm		
			STEL 5.0 ppm		
Toxics (EC Sensors)					
Ammonia (NH₃)	0 - 400.0 ppm	0.5 ppm	A1: 25 ppm	± 10% of reading or ± 5% of full scale	
			A2: 50 ppm		
Chlorine (Cl₂)	0 - 10.00 ppm	0.05 ppm	A1: 0.5 ppm		
			A2: 1.0 ppm		
Hydrogen Cyanide (HCN)	0 - 15.0 ppm	0.1 ppm	A1: 5 ppm		
			A2: 10 ppm		
Nitrogen Dioxide (NO₂)	0 - 20.00 ppm	0.05 ppm	A1: 3 ppm		
			A2: 6 ppm		
	0 - 99.90 ppm		A1: 2 ppm		
			A2: 5 ppm		
IR Sensors					
Carbon Dioxide (CO₂)	0 - 10,000 ppm	20 ppm	A1: 5,000 ppm	± 5% of reading or ± 2% of full scale	
			TWA 5,000 ppm		
	0 - 10.00% Vol.	0.02%	A1: 0.50% Vol		
			A2: 3.00% Vol		
			STEL 3.00% Vol		
Methane (CH₄)	0 - 100% LEL 0 - 100% Vol.	Vol. 1% LEL/ 0.5% Vol	A1: 10% LEL A2: 50% LEL		
Hydrocarbons	0 - 100% LEL 0 - 30% Vol				
PID Sensors					
10.6 Lamp	600 VOC's	0 - 50,000 ppb	1 ppb: (< 5000 ppb) 10 ppb: (> 5,000 ppb)	A1: 5,000 ppb	± 5% of full scale
			A2: 10,000 ppb		
		0 - 6,000 ppm	0.1 ppm: (< 600 ppm) 1 ppm: (> 600 ppm)	A1: 400 ppm	
			A2: 1,000 ppm		
10.0 Lamp	Benzene Specific	0.1 - 50 ppm	0.01 ppm (0 ~ 10 ppm) 0.1 ppm (10 ~ 50 ppm)	No Alarms	
	300 VOC's	0 - 100 ppm	0.01 ppm (0 ~ 10 ppm) 0.1 ppm (10 ~ 100 ppm)	A1: 5 ppm A2: 10 ppm	

Common Specifications			
Alarm Types	Gas alarm	Man-down	Trouble
	Low and high adjustable	1st - self reset 2nd - latching	Low flow Sensor connection Low battery Circuit error Calibration range
Sample Method	Sample draw pump, flow rate 0.45 LPM, 50 foot sample range		
Display	Digital LCD, autobacklite, peak bar display, auto display rotation, and customize order of gases		
Audible Alarm	95 dB at 1 ft.		
Languages	English, Spanish, French, German, Italian, Japanese, Korean, Portuguese, Russian		
Continuous Operation	14 hours on Lithium-ion battery pack. Complete recharge in 3 hours. 8 hours Alkaline battery pack (3 AA size within each pack)		
Operating Temp. & Humidity	-4 °F to 122 °F (-20 °C ~ +50 °C), 0- 95% RH non condensing		
Dimensions	2.6" W x 7.8" H x 2" D (H200 x W68 x D52 mm) 14 ounce (400g) (with lithium battery pack)		
Case Material	Dust and water resistant with IP-67 approval (exclude sample hose and probe)		
Safety Design / Approvals	Explosion proof: IECEx , ATEX , TIIS , cCSAus Explosion class :Ex ia IIC T4 Ga Others: CE Marking		
Standard Features	2 Smart sensors slots auto recognize sensor changes Library of over 600 VOC's User defined VOC list. Up to 30 frequently used Recent VOC list for last 8 selected gases Pump and circuit status indicators User & station ID selection menu Datalogging (interval, alarm trend, station and user ID) Snap logging - on demand data logging Demand zero / Auto zero BUMP and CAL expiration alarm Flashlight IrDA communication LEL sensor protection mode		
Standard Accessories	<ul style="list-style-type: none"> • Rubber boot • Hand strap • Probe with hydrphobic & dust filter 3' teflon lined hose • Benzene pre-filter tubes and holder (benzene versions) • Belt clip • Tapper nozzle 		
Optional Accessories	<ul style="list-style-type: none"> • SDM-6000 calibration station • Bundles with instrument carrying case and accessories • Flexible probes • Up to 40 foot sample hoses • Filter set • IrDA cable 		
Warranty	Two years material (including sensors) and workmanship. One year for PID sensor		